

SPECIFICATION MANUAL 2024

SPECIFICATIONS OF EQUIPMENT



stagethreeengineering.com



TABLE OF CONTENT

FORKLIFTS

TREE LOADERS

SCISSOR LIFTS

EXCAVATORS

SKID STEERS

WHEEL LOADERS



S3E FORKLIFTS

SPECIFICATIONS

MODEL

S3E 4WD ALL TERRAIN

LENGTH

15 feet 5 inches

WIDTH

5 feet 11 inches

HEIGHT

8 feet 4 inches

FORK LENGTH

4 feet

OPERATING WEIGHT

11,499 lbs

WHEEL BASE

5 feet

ENGINE

Cummins QSF 2.8 74

FUEL TYPE

Diesel

HORSEPOWER

55 HP

LIFTING HEIGHT

14 feet 9 inches

DRIVE MODE

4WD





MULTI USE TREE LOADERS

SPECIFICATIONS

MODEL

4WD MULTI USE TREE LOADER

LENGTH

12.38 feet

WIDTH

4.10 feet

HEIGHT

7.55 feet

WEIGHT

4,850 lbs

STANDARD WHEELS

27/10.5-1.5(26/12-12)

TRANSMISSION DRIVE

Hydrostatic

DRIVE SPEED MAX

7 mph

ENGINE MAKE AND TYPE

Kubota V1505 Diesel

ENGINE OUTPUT

25 HP

TORQUE MAX (LB-FT/RPM)

92.6 (68.3)/1700

LIFT HEIGHT

14 feet

LIFT CAPACITY

2300 lbs





S3E ELECTRIC SCISSORLIFTS

SPECIFICATIONS

MODEL

ELECTRIC SCISSOR LIFT

PLATFORM SIZE

6 feet by 2 feet

LENGTH

6 feet

WIDTH

2 feet by 6 inches

HEIGHT

6 feet by 9 inches

LIFT HEIGHT

20 feet

WEIGHT

5070 lbs

SAFE WORKING LOAD

705 lbs

LIFTING MOTOR BATTERY

24 Volt

BATTERY

6 Volt

WHEEL TYPE

Roller



S3E EXCAVATORS

SPECIFICATIONS

MODEL

1 Ton

4 Ton

ENGINE

Briggs and Stratton

Kubota D1703

HORSEPOWER

13 HP

30 HP

FUEL TYPE

Gasoline

Diesel

LENGHT

9 feet

16 feet

WIDTH

3 feet 1 inch

5 feet 7 inch

HEIGHT

3 feet

8 feet 3 inches

OPERATING WEIGHT

2,205 lbs

8,800 lbs

ARM EXTENSION LENGHT

2 feet 4 inches

4 feet 7 inches

ARM EXTENSION HEIGHT

5 feet

8 feet

TRACK WIDTH

7 inches

11.8 inches



WHEEL LOADERS

SPECIFICATIONS

MODEL

RATED BUCKET CAPACITY

HOPPER WIDTH

RATED LOAD

TOTAL WEIGHT

ENGINE TYPE

POWER OF ENGINE

DUMPING HEIGHT

DUMPING REACH

MINIMUM GROUND CLEARNACE

MINIMUM TURNING

UNLOADING ANGLE

TIRE

DISTANCE BETWEEN AXLES

DISTANCE BETWEEN WHEELS

TRANSMISSION ASSEMBLY

WHEEL LOADER

14.13 feet

53.15 feet

1,764 lbs

5,584 lbs

Kubota

24.65 HP

90.55 in

27.17 in

8.66 in

189 in

37 degrees

31-15.5-15

75 in

45.28 in

240

SKID STEERS

SPECIFICATIONS

MODEL

STACETHE

MINI SKID STEER

Lenght

9.51 feet

Width

3.5 feet

Height

5 feet

Weight

3,417 lbs

Track Width

7 inches

Transmission Drive

Drive Speed Max

4.3 mph

Engine Make and Type

Kubota V1505

Engine Output

24 HP

Torque Max

1,700 RPM

Bucket Capacity

7 Cubic feet



CONTACT



888-933-5773



sales@stagethreeengineering.com



stagethreeengineering.com